



FLOWTRAK II



FLOW MONITORING SYSTEM

Eliminate Uncertainty.
Apply with **CONFIDENCE...**

An electronic flow monitoring system designed to help your operation produce maximum yields and work more cost-effectively. It provides the critical flow information you need to maintain ideal application rates of liquid chemicals and fertilizer.

Achieve your target rate with consistency, and on-the-mark accuracy.

Micro-Trak Systems Inc.
800-328-9613
Micro-Trak.com
Trakmail@Micro-Trak.com

WHAT SETS US APART:

- Partner/Listen/Customize
- 3-year warranty
- Loaner program

 **MICRO-TRAK**
INNOVATIVE FROM THE GROUND UP
Copyright © 2021 • Micro-Trak® Systems, Inc. • All Rights Reserved

FLOWTRAK II SYSTEM OPTIONS

ASTRO™ - GPS SPEED SENSORS



Two models to choose from: the economical Astro™ II (1 Hz), or super-fast Astro™ 5 (5 Hz)

- Boost productivity and efficiency
- Flexible mounting options
- Rugged design consistently performs

MAGNETIC FLOWMETERS



MM53
1" FPT
2.6-53 GPM
290 PSI Max.

Advantages:

- No internal moving parts
- Unaffected by fluid viscosity and density
- Highly accurate
- Saves time and money; very low maintenance

MODEL - FLOW RANGE - SIZE:

MM2 - .08 to 1.6 gpm, 3/4" FPT
MM3 - .13 to 2.6 gpm, 3/4" FPT
MM5 - .3 to 5 gpm, 3/4" FPT
MM13 - .6 to 13 gpm, 3/4" FPT
MM26 - 1.3 to 26 gpm, 1" FPT
MM53 - 2.6 to 53 gpm, 1" FPT
MM106 - 5 to 106 gpm, 1 1/2" FPT
MM106FL - 5 to 106 gpm, M200 flange
MM158 - 8 to 158 gpm, 2" MPT
MM238 - 12 to 238 gpm, 2" MPT

(All models max. pressure rated to 290 psi @ 70°F)

TURBINE FLOWMETERS

FM250 P

1/4" BSP
w/ 1/2" hosebarb
.08-1.6 GPM
290 PSI Max.



FM500

1/2" FPT

.5-5 GPM
500 PSI Max.



FM750 LF GFN

3/4" FPT

.5-12 GPM
150 PSI Max.



FM750 GFN

3/4" FPT

2-40 GPM
150 PSI Max.



FM750 LF SS

3/4" FPT

1-9 GPM
500 PSI Max.



FM750 SS

3/4" FPT

2-40 GPM
500 PSI Max.



FM1000 SS

1" FPT

3.5-70 GPM
500 PSI Max.



FM1500 LF SS

1 1/2" FPT

3.5-70 GPM
500 PSI Max.



FM1500 SS

1 1/2" FPT

10-130 GPM
500 PSI Max.



FM270 LF

2" flange
(M200)

.5-15 GPM
225 PSI Max.



FM270

2" flange
(M200)

3.5-70 GPM
225 PSI Max.



FM10-100

2" flange
(M200)

10-100 GPM
225 PSI Max.



FM2000 P

2" flange
(M200)

19-198 GPM
285 PSI Max.



FM3000 P

3" MPT

40-396 GPM
285 PSI Max.



(All pressure ratings @ 70°F)

WHAT SETS US APART:

- Partner/Listen/Customize
- 3-year warranty
- Loaner program

