

SprayMate™ II

Simple Precision.

The SprayMate™ II features a self-contained design with built-in controls for up to 3 separate boom sections. It regulates rates of application precisely, regardless of changing field conditions. Spray or apply NH₃ with certainty as the SprayMate™ II applies the right amount —

Right Where You Need It.



See reverse for system options →



MICRO-TRAK[®]
SYSTEMS, INC.

Creating Innovative Solutions Since 1982.

Eagle Lake, MN • www.micro-trak.com • (800)328-9613

System Options

Liquifier™ Series

High Capacity NH3 Heat Exchangers



- Tough stainless-steel construction
- No seasonal maintenance
- Pre-assembled, tested, and ready to bolt on

4 sizes to perfectly match your application needs.

Liquifier™Max • Liquifier™

Liquifier™Junior • Liquifier™Ultra Low Rate

Astro™ - GPS Speed Sensors



Two models to choose from: the economical Astro™ II (1 Hz), or super-fast Astro™ 5 (5 Hz)

- Boost productivity and efficiency
- Flexible mounting options
- Rugged design consistently performs

Hydraulic Flow Control Valves

- Internally protected, economical, safe, flexible, efficient, and easy to use!
- Reduces pump wear
- Ideal for open, closed, or load sense systems
- Available in 12VDC standard or PWM configurations



Standard

PWM

Servo Valves

Flanged



12VDC
2" Flange or
1.5" FPT

Threaded



12VDC
1" FPT

9 servo valve models to fit your flow control needs — including high-pressure (300 psi) and NH3 ready versions.

Turbine Flowmeters

Rugged, Reliable, and Accurate

FM500

.50" FPT

.5-5 GPM
500 PSI Max.



FM750 GFN

.75" FPT

2-40 GPM
150 PSI Max.



FM750 LF GFN

.75" FPT

.5-12 GPM
150 PSI Max.



FM750 SS

.75" FPT

2-40 GPM
500 PSI Max.



FM750 LF SS

.75" FPT

1-20 GPM
500 PSI Max.



FM1000 SS

1" FPT

3.5-70 GPM
500 PSI Max.



FM1500 SS

1.5" FPT

10-130 GPM
500 PSI Max.



FM1500 LF SS

1.5" FPT

3.5-70 GPM
500 PSI Max.



FM270

2" flange

3.5-70 GPM
125 PSI Max.



FM10-100

2" flange

10-100 GPM
125 PSI Max.



FM2000 P

2" flange

19-198 GPM
285 PSI Max.



FM3000 P

3" MPT

40-396 GPM
285 PSI Max.



Magnetic Flowmeters



MM3 - 3/4" FPT



MM238 - 2" MPT

8 models - ranging from .3 to 238 gpm max.

Electric Pump Drivers

- Controls flow rate by regulating the speed of a 12VDC pump
- Ideal for low-rate applications such as liquid starter fertilizer on drills and planters
- Controls most 12VDC pumps up to a max of 60 amps
- 12v Standard DC and PWM versions available

